



RMTDU



3U 19" Triple-screen Rack-mount LCD

Technical Specifications

| PRODUCT | RMTDU |
|------------------|--|
| DISPLAY | 3X 19" SXGA 1280 X 1024 |
| VIEWING ANGLE | DISPLAYS TILT ~15° FROM VERTICAL |
| PORTS | 1X VGA, 1X DVI, 1X DP, AND 2X USB |
| POWER SUPPLY | 115/230 VAC, 50/60 HZ, 75W MAX |
| KEYBOARD & MOUSE | 101 KEYS BACKLIT KEYBOARD WITH TOUCHPAD AND ADJUSTABLE BRIGHTNESS + RESISTIVE TOUCHPAD |
| DIMENSIONS | HEIGHT: 3U - 5.13" (130MM), WIDTH: 19" (482.6MM), DEPTH: 25.8" (655MM) |
| WEIGHT | ~58LBS (26KG) |
| TEMPERATURE | MIL-STD-810E (501.4, 502.4), OPERATING: 0 ~ 50°C, NON-OPERATING: -40 ~ 70°C |
| HUMIDITY | MIL-STD-810E (507.2), RELATIVE HUMIDITY: 5% TO 95% OPERATING, NON-CONDENSING |

* The technical specifications are an example of the system's capabilities. They can be customized specifically for your needs. If you have any questions, feel free to contact one of our sales representatives.



Headquarters - USA

ACME Portable Machines, Inc.
1330 Mountain View Circle,
Azusa, CA, 91702, USA
Tel: +1 626.610.1888
Fax: +1 626.610.1881
www.acmeportable.com

Germany

ACME Portable Computer GmbH
Benzstraße 15,
76185 Karlsruhe, Germany
Tel: +49.721.570.4530
Fax: +49.721.570.45329
www.acmeportable.de

Taiwan

ACME Portable Corp.
5F, No 25, Wuquan 3rd Road,
Wugu Dist., New Taipei City 248,
Taiwan R.O.C
Tel: +886.2.2298.3636
Fax: +886.2.2298.3737
www.acmeportable.com.tw