



RNA 248-10R



ACME Portable's rugged network appliances are Gigabit Ethernet Layer 2 and Layer 3 access switches. They are built to be easy to deploy, manage, and troubleshoot.

Technical Specifications

PRODUCT	RNA 248-10R
PORTS	48 MAXIMUM SWITCHED ETHERNET LAN PORTS WITH POE
MEMORY	16 GB
POWER SUPPLY	120/230 V, 50/60 HZ
HUMIDITY	(OPERATING) 10 - 95% (NON-CONDENSING), (STORAGE) 10 - 95% (NON-CONDENSING)
TEMPERATURE	(OPERATING) 23 °F ~ 113 °F
STORAGE	(STORAGE) -13 °F ~ 158 °F

* The technical specifications are an example of the system's capabilities. They can be customized specifically for your needs. If you have any questions, feel free to contact one of our sales representatives.



Headquarters - USA

ACME Portable Machines, Inc.
1330 Mountain View Circle,
Azusa, CA, 91702, USA
Tel: +1 626.610.1888
Fax: +1 626.610.1881
www.acmeportable.com

Germany

ACME Portable Computer GmbH
Benzstraße 15,
76185 Karlsruhe, Germany
Tel: +49.721.570.4530
Fax: +49.721.570.45329
www.acmeportable.de

Taiwan

ACME Portable Corp.
5F, No 25, Wuquan 3rd Road,
Wugu Dist., New Taipei City 248,
Taiwan R.O.C
Tel: +886.2.2298.3636
Fax: +886.2.2298.3737
www.acmeportable.com.tw